#### **ABSTRACT**

The invention relates to a technique for forming a thin film of good quality on a base substance via an intermediate layer. Such a film formation technique is suitably applicable to formation of an oxide high-temperature superconductor thin film usable for a superconducting wire material, a superconducting device or the like.

5

10

In the method of forming a thin film on a base substance via an intermediate layer, an interface energy Ea at an interface A between the base substance and the intermediate layer, an interface energy Eb at an interface B between the intermediate layer and the thin film, and an interface energy Ec at an interface C between the base substance and the thin film in a state where the intermediate layer is omitted are calculated, and then a substance for the intermediate layer is selected so as to satisfy conditions of Ea<Ec and Eb<Ec.

### (12)特許協力条約に基づいて公開された国際出願

### (19) 世界知的所有権機関 国際事務局



# 07 MAR 2005

(43) 国際公開日 2004 年5 月13 日 (13.05.2004)

**PCT** 

## (10) 国際公開番号 WO 2004/040046 A1

(51) 国際特許分類7:

C30B 29/22, H01L 39/24

(21) 国際出願番号:

PCT/JP2003/013887

(22) 国際出願日:

2003年10月29日(29.10.2003)

(25) 国際出願の言語:

日本語

(26) 国際公開の言語:

日本語

(30) 優先権データ: 特願 2002-318477

2002年10月31日(31.10.2002) 月

(71) 出願人(米国を除く全ての指定国について): 住友電 気工業株式会社 (SUMITOMO ELECTRIC INDUS-TRIES, LTD.) [JP/JP]; 〒541-0041 大阪府 大阪市 中 央区北浜四丁目5番33号 Osaka (JP). 財団法人国際 超電導産業技術研究センター (INTERNATIONAL SUPERCONDUCTIVITY TECHNOLOGY CENTER, THE JURIDICAL FOUNDATION) [JP/JP]; 〒105-0004 東京都港区新橋5丁目34番3号 栄進開発ビル6階 Tokyo (JP).


(72) 発明者; および


(75) 発明者/出願人 (米国についてのみ): 長谷川 勝哉 (HASEGAWA,Katsuya) [JP/JP]; 〒135-0062 東京都 江東区東雲1丁目10番13号 財団法人国際超電導産業技術研究センター 超電導工学研究所内 Tokyo (JP). 和泉輝郎 (IZUMI,Teruo) [JP/JP]; 〒135-0062 東京都 江東区東雲1丁目10番13号 財団法人国際超電導産業技術研究センター 超電導工学研究所内 Tokyo (JP). 塩原融 (SHIOHARA,Yuh) [JP/JP]; 〒135-0062 東京都 江東区東雲1丁目10番13号 財団法人国際超電導産

/続葉有/

## (54) Title: METHOD FOR FORMING THIN FILM ON BASIC MATERIAL THROUGH INTERMEDIATE LAYER

(54) 発明の名称: 基材上に中間層を介して薄膜を形成する方法





(57) Abstract: A technology for forming a thin film of good quality on a basic material through an intermediate layer. The technology is applied preferably to the formation of a high-temperature superconducting oxide thin film being employed in a superconducting wire material or a superconducting device. The method for forming a thin film on a basic material through an intermediate layer is characterized by comprising a process for calculating the energy Ea on the interface A between the basic material and the intermediate layer, the energy Eb on the interface B between the intermediate layer and the thin film, and the energy Ec on the interface C between the basic material and the thin film under a state where the intermediate layer does not exist, and a process for selecting an intermediate layer material satisfying the conditions Ea<Ec and Eb<Ec.

- a...DISPLACEMENT FROM ATOMIC POSITION OF PERFECT CRYSTAL (%)
- p...Sm123/MgO(Ba ON Mg)
- C...BETWEEN ATOMS STRADDLING INTERFACE
- d...Sm123/BZO(Ba IN BZO)